

# URINALS

## Siphonic urinal ANTERO 84015.0



### TECHNICAL DATA

|                     |  |
|---------------------|--|
| Order no.           | 84015.0<br>Charge 000 (DN 40) / Charge 401 (DN 50)   |
| Certified to        | DIN 1390, EN 13407   |
| matching for        | LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5  |
| Specification       | 1-l flushing electronic controlled siphonic urinal<br>HF Electronic control for battery (6x AA 1,5 V) pre-assembled<br>Ceramic siphon cover<br>Siphon replaceable without dismantling urinal<br>1-l flushing automatic adjusted independent of supply pressure<br>Lid under urinal<br>Waste piping cleaning without dismantling urinal only in combination with fixing set order no. 89282.6<br>Charge 000 – DN 40<br>Charge 401 – DN 50 |
| Water inlet         | concealed, 1/2"  |
| Outlet              | horizontal   |
| Flushing            | minimum 0.5 l - 3.0 l  |
| Flushing rate       | minimum 0.3 l/s  |
| Weight              | 25,0 kg  |
| Mounting acc. incl. | Electronic control pre-assembled<br>Ceramic siphon cover, order no. 89818.9<br>laufen EasyFit system M8, order no. 89282.6   |

|                     |   |
|---------------------|---|
| Mounting acc. incl. | 1-liter siphon, order no. 89419.3<br>Charge 000 – waste connection pipe DN 40, order no. 89419.4<br>Charge 401 – waste connection pipe DN 50, order no. 89419.5                                       |
| Mounting acc. excl. | 1-liter spare part siphon, order no. 89419.6<br>Adaption set for stone screws M10, order no. 89281.6<br>Adaption set for stone screws M12, order no. 89281.4<br>USB Adapter module, order no. 89013.0 |
| Colours             | see colour table  |

### SPECIFICATION TEXT

Siphonic urinal Laufen-ANTERO, sanitary ceramic, electronic controlled, DIN 1390, EN 13407, dimensions 380 x 365 x 770 mm min. 0.5 l - 3.0 l flushing automatic adjusted independent of supply pressure, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal, flushing rate minimum 0.3 l/s HF electronic control for battery (6x AA 1,5 V) pre-assembled, siphon replaceable without dismantling urinal, lid under urinal, waste piping cleaning without dismantling urinal  
Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)  
Further options / accessories: 1-liter spare part siphon, LIS CU3 concealed frame for urinal with integrated control  
Order no. 84015.0

### TECHNICAL DRAWINGS / S 1 : 20

