

**Siphonic urinal  
LEMA  
84019.7**



**TECHNICAL DATA**

Order no.	84019.7 Charge 000 (DN 40) / Charge 401 (DN 50)
Certified to	EN 80
matching for	LIS CU2 Concealed frame for urinal without integrated control, order no. 89266.4 LIS SMART CONTROL-U, order no. 37066.0
Specification	1-l flushing siphonic urinal Ceramic siphon cover Siphon replaceable without dismantling urinal Only in combination with fixing set, order no. 89280.8 Charge 000 – DN 40 Charge 401 – DN 50
Water inlet	concealed 1/2"
Outlet	horizontal
Flushing	minimum 0.5 l - 3.0 l
Flushing rate	minimum 0.3 l/s
Weight	24,5 kg
Mounting acc. incl.	Ceramic siphon cover, order no. 89818.9 Wall fixing set M8 LAUFEN, order no. 89280.8 1-liter siphon, order no. 89313.4 Charge 000 – waste connection pipe DN 40, order no. 89419.4 Charge 401 – waste connection pipe DN 50, order no. 89419.5

Mounting acc. excl.	LIS CU2 horizontal inlet connection, order no. 89009.7 1-liter spare part siphon, order no. 89313.4 Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
Colours	see colour table

**SPECIFICATION TEXT**

Siphonic urinal Laufen-LEMA, sanitary ceramic EN 80, dimensions 350 x 400 x 700 mm minimum 0.5 l - 3.0 l flush, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal, flushing rate minimum 0.3 l/s siphon replaceable without dismantling urinal, Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)  
Further options / accessories: LIS horizontal inlet connection, 1-liter spare part siphon, LIS CU2 concealed frame for urinal without integrated control  
Order no. 84019.7

**TECHNICAL DRAWINGS / S 1 : 20**

